

BET 40



FEATURES

20 pints Glass Capacity
Automatic Rinseaid Injection
Automatic Detergent Injection
Stainless Steel Construction
Safety Cut - Out Door Switch
2 x Glass Baskets Supplied

OTHER

Water Pressure Requirement - min 2 bar / max 5 bar
Usage at 3 bar approx 3ltr per cycle
Operating Temperature - Wash 60°C / Rinse 85°C

Model

Model	Basket Size mm	Dimensions mm H x W x D	Cycle Time min	Cold Rinse	Door Opening Height mm
BET 40	400 x 400	600 x 480 x 480	2	No	250
BET 40 DP	400 x 400	600 x 480 x 520	2	No	250

Electrical

Wash Pump load	Tank Heater load	Boiler Heater load	Total Electrical load	Voltage
0.2 Hp	2000W	2000W	2250W / 10 Amps	230V

Accessories

Item	Description	Code	RRP £
Water Softener	Use in medium/hard water areas to help prevent the build up limescale	LT8	80.00
		LT12	85.00
Adjustable Stand	530 h/mm Black painted steel 300 h/mm Black painted steel	STAND	70.00
		STANDSML	56.00
Baskets	Glass Basket	4173	30.52
Rinse Booster Pump (External)	For low pressure or hot water supply (max 50°C)	4809	209.48
Drip Trays	For Racking System	DT40	24.00

ALL PRICES EXCLUDE DELIVERY & VAT