

OMEGA



FEATURES

22 Plate Rack Capacity
 Automatic Rinseaid Injection
 Automatic Detergent Injection
 Integral Rinse Booster Pump on Breaktank Model
 Double Skinned Stainless Steel Construction
 Primary & Secondary Wash Tank Filter
 Safety Cut - Out Door Switch
 1 x Plate Rack, 1 x Cup Basket,
 1 x Saucer Insert & 4 x Cutlery Inserts Supplied
 3 Phase with Options to order

OTHER

Water Pressure Requirement - min 2 bar / max 5 bar
 Usage at 3 bar approx 3ltr per cycle
 Operating Temperature - Wash 60°C / Rinse 85°C

Model

| Model | Basket Size mm | Dimensions mm H x W x D | Cycle Time min | Cold Rinse | Door Opening Height mm |
|------------|-------------------|-------------------------------|-------------------|------------|------------------------------|
| Omega | 500 x 500 | 825 x 600 x 600 | 2 | No | 330 |
| Omega DP | 500 x 500 | 825 x 600 x 600 | 2 | No | 330 |
| Omega BT | 500 x 500 | 825 x 600 x 640 | 2 | No | 330 |
| Omega DPBT | 500 x 500 | 825 x 600 x 640 | 2 | No | 330 |

Electrical

| Wash Pump load | Tank Heater load | Boiler Heater load | Total Electrical load | Voltage |
|----------------|------------------|--------------------|-----------------------|---------|
| 0.75 Hp | 3000W | 4500W | 5050KW / 22 Amps | 230V |

Accessories

| Item | Description | Code | RRP £ |
|-------------------------------|---|----------|--------|
| Water Softener | Use in medium/hard water areas to help prevent the build up limescale | LT8 | 80.00 |
| | | LT12 | 85.00 |
| Adjustable Stand | 530 h/mm Black painted steel 300 h/mm Black painted steel | STAND | 70.00 |
| | | STANDSML | 56.00 |
| Baskets | Plate Rack 22 position Cup Basket Saucer Insert Cutlery Insert | 3210 | 41.54 |
| | | 3211 | 48.16 |
| | | 4166 | 10.12 |
| | | 4167 | 5.52 |
| Rinse Booster Pump (External) | For low pressure or hot water supply (max 50°C) | 4809 | 209.48 |
| Drip Trays | For Racking System | DT50 | 26.00 |

ALL PRICES EXCLUDE DELIVERY & VAT