

# SINCRO



## FEATURES

25 Pints Glass Capacity  
 16 Plate Rack Capacity  
 Automatic Rinseaid Injection  
 Automatic Detergent Injection  
 Double Skinned Stainless Steel Construction  
 Safety Cut - Out Door Switch  
 2 x Glass Baskets  
 or  
 1 x Plate Rack, 1 x Cup Basket,  
 1 x Saucer Insert & 2 x Cutlery Inserts Supplied

## OTHER

Water Pressure Requirement - min 2 bar / max 5 bar  
 Usage at 3 bar approx 3ltr per cycle  
 Operating Temperature - Wash 60°C / Rinse 85°C

## Model

Model	Basket Size mm	Dimensions mm H x W x D	Cycle Time min	Cold Rinse	Door Opening Height mm
Sincro	450 x 450	775 x 550 x 550	2	Yes	280
Sincro DP	450 x 450	775 x 550 x 550	2	No	280

## Electrical

Wash Pump load	Tank Heater load	Boiler Heater load	Total Electrical load	Voltage
0.5 Hp	2000W	3000W	3350W / 15 Amps	230V

## Accessories

Item	Description	Code	RRP £
Water Softener	Use in medium hard/hard water areas to help prevent the build up limescale	LT8	80.00
		LT12	85.00
Adjustable Stand	530 h/mm Black painted steel 300 h/mm Black painted steel	STAND	70.00
		STANDSML	56.00
Baskets	Plate Rack 16 position Glass / Cup Basket Saucer Insert Cutlery Insert	4188	40.44
		4187	40.44
		4166	10.12
		4167	5.52
Rinse Booster Pump (External)	For low pressure or hot water supply (max 50°C)	4809	209.48
Drip Trays	For Racking System	DT45	25.00

**ALL PRICES EXCLUDE DELIVERY & VAT**