

TECHNICAL SPECIFICATIONS

	Micro & Micro+	Bet 40	Sincro	Logos	Omega	Compact
Cycle time	2 mins	2 mins	2 mins	2 mins	2 mins	1 or 2 mins
Rack size	370x370	400x400	450x450	500x500	500x500	500x500
WASH CAPACITY						
Glasswashers	16 pints	20 pints	25 pints	30 pints	--	--
Dishwashers	--	--	14 plates	16 plates	22 plates	22 plates
MACHINE DIMENSIONS						
Height	500/550	600	775	825	825	1450 (1895 max)
Width	450	480	550	600	600	650 (710 max)
Depth (door closed)	450	480/520	550	600	600	775
Depth (door open)	750/800	820/860	940	1020	1020	--
Depth with breaktank	--	--	575	--	640	--
Usable door opening height	200/250	250	290	330	330	400
ELECTRICAL SPECIFICATIONS						
Boiler heater loading	2000 W	2000 W	3000 W	3000 W	4500 W	6000 W
Tank heater loading	2000 W	2000 W	2000 W	2000 W	3000 W	3000 W
Wash pump power	Hp 0.2	Hp 0.2	Hp 0.5	Hp 0.75	Hp 0.75	Hp 1.2
Total rating	2300 W	2300 W	3600 W	3800 W	5400 W	6900W
Voltage	230	230	230	230	230/400	230/400
Ampage	10	10	16	17	24/16	30/16
OTHER INFORMATION						
Boiler capacity	2 lt	4 lt	5 lt	6 lt	6 lt	6.5 lt
Tank capacity	12 lt	6.5 lt	18 lt	24 lt	24 lt	27 lt
Water use at 3 bar	3 lt	3 lt	3 lt	3 lt	3 lt	3.5 lt
Water supply pressure	3-5 bar	3-5 bar	3-5 bar	3-5 bar	3-5 bar	3-5 bar
BASKETS PROVIDED WITH GLASSWASHERS						
Flat baskets	2	2	2	2	--	--
BASKETS AND RACKS PROVIDED WITH DISHWASHERS						
Flat baskets	--	--	1	1	1	1
Plate rack	--	--	1	1	1	2
Saucer rack	--	--	1	1	1	2
Cutlery basket	--	--	2	4	4	4
FEATURES / OPTIONS AVAILABLE ■ = STANDARD ▼ = EXTRA COST OPTION						
Stainless steel construction	■	■	■	■	■	■
Double skinned construction	--	--	■	■	■	--
Safety cut-out door switch	■	■	■	■	■	■
Automatic rinse aid injection	■	■	■	■	■	■
Built-in auto detergent injection	--	■	■	■	■	■
Pre-wired for detergent injection	■	--	--	--	--	--
Secondary wash tank filter	--	--	--	▼	■	■
Built-in drainer pump	--	▼	▼	▼	▼	--
Built-in breaktank	--	--	▼	--	▼	▼

All dimensions are in millimetres unless otherwise stated. 'Pints' refers to 20oz Nonic (pint to rim) glasses. E&OE